



AP[®] Physics C: Mechanics 2004 Sample Student Responses


The materials included in these files are intended for noncommercial use by AP teachers for course and exam preparation; permission for any other use must be sought from the Advanced Placement Program[®]. Teachers may reproduce them, in whole or in part, in limited quantities, for face-to-face teaching purposes but may not mass distribute the materials, electronically or otherwise. This permission does not apply to any third-party copyrights contained herein. These materials and any copies made of them may not be resold, and the copyright notices must be retained as they appear here.

The College Board is a not-for-profit membership association whose mission is to connect students to college success and opportunity. Founded in 1900, the association is composed of more than 4,500 schools, colleges, universities, and other educational organizations. Each year, the College Board serves over three million students and their parents, 23,000 high schools, and 3,500 colleges through major programs and services in college admissions, guidance, assessment, financial aid, enrollment, and teaching and learning. Among its best-known programs are the SAT[®], the PSAT/NMSQT[®], and the Advanced Placement Program[®] (AP[®]). The College Board is committed to the principles of excellence and equity, and that commitment is embodied in all of its programs, services, activities, and concerns.

For further information, visit www.collegeboard.com

Copyright © 2004 College Entrance Examination Board. All rights reserved. College Board, Advanced Placement Program, AP, AP Central, AP Vertical Teams, APCD, Pacesetter, Pre-AP, SAT, Student Search Service, and the acorn logo are registered trademarks of the College Entrance Examination Board. PSAT/NMSQT is a registered trademark of the College Entrance Examination Board and National Merit Scholarship Corporation. Educational Testing Service and ETS are registered trademarks of Educational Testing Service. Other products and services may be trademarks of their respective owners.

For the College Board's online home for AP professionals, visit AP Central at apcentral.collegeboard.com.



Mech. 3.

A uniform rod of mass M and length L is attached to a pivot of negligible friction as shown above. The pivot is located at a distance $\frac{L}{3}$ from the left end of the rod. Express all answers in terms of the given quantities and fundamental constants.

(a) Calculate the rotational inertia of the rod about the pivot.

$$\lambda = \frac{M}{L} \quad dm = \lambda dx = \frac{M}{L} dx$$

$$I = \sum mr^2 = \int_0^{\frac{2}{3}L} \frac{M}{L} dx \cdot x^2 + \int_{\frac{L}{3}}^L \frac{M}{L} dx \cdot x^2$$

$$= \frac{M}{L} \int_0^{\frac{2}{3}L} x^2 dx + \frac{M}{L} \int_{\frac{L}{3}}^L x^2 dx$$

$$= \frac{M}{L} \left(\frac{x^3}{3} \Big|_0^{\frac{2}{3}L} \right) + \frac{M}{L} \left(\frac{x^3}{3} \Big|_{\frac{L}{3}}^L \right)$$

$$= \frac{M}{L} \left(\frac{2^3 L^3}{3} + \frac{L^3}{3} \right)$$

$$= \frac{ML^2}{9}$$

(b) The rod is then released from rest from the horizontal position shown above. Calculate the linear speed of the bottom end of the rod when the rod passes through the vertical.

$$h = \frac{2}{3}L \quad h_1 = \frac{1}{2}L \quad \omega = \frac{v}{\frac{2}{3}L} \Rightarrow v = \frac{2}{3}L \cdot \omega$$

$$U_i + K_i = U_f + K_f$$

$$Mgh + 0 = Mgh_1 + \frac{1}{2}I\omega^2$$


$$Mg \cdot \frac{2L}{3} = Mg \cdot \frac{L}{2} + \frac{1}{2} \cdot \frac{ML^2}{9} \cdot \omega^2$$

$$4MgL = 3MgL + \frac{ML^2}{3} \omega^2$$

$$\Rightarrow \frac{ML^2 \omega^2}{3} = MgL \Rightarrow \omega^2 = \frac{3MgL}{ML^2} \Rightarrow \omega = \sqrt{\frac{3g}{L}}$$

$$\Rightarrow v = \frac{2L}{3} \cdot \sqrt{\frac{3g}{L}} = \sqrt{\frac{4L^2}{9} \cdot \frac{3g}{L}} = \sqrt{\frac{4Lg}{3}}$$

GO ON TO THE NEXT PAGE.




(c) The rod is brought to rest in the vertical position shown above and hangs freely. It is then displaced slightly from this position. Calculate the period of oscillation as it swings.

$$\omega = \sqrt{\frac{Mgd}{I}} \Rightarrow T = \frac{2\pi}{\omega} = 2\pi \sqrt{\frac{I}{Mgd}}$$

$$d = \frac{L}{2} - \frac{L}{3} = \frac{L}{6}$$

$$\Rightarrow T = 2\pi \sqrt{\frac{\frac{ML^2}{9}}{Mg \frac{L}{6}}} = 2\pi \sqrt{\frac{ML^2}{9} \cdot \frac{6}{MgL}} = 2\pi \sqrt{\frac{2L}{3g}}$$



Mech. 3.

A uniform rod of mass M and length L is attached to a pivot of negligible friction as shown above. The pivot is located at a distance $\frac{L}{3}$ from the left end of the rod. Express all answers in terms of the given quantities and fundamental constants.

(a) Calculate the rotational inertia of the rod about the pivot.

Handwritten: Rod's inertia around center of mass: $\frac{1}{12} mL^2$

$$\frac{1}{12} mL^2 + m \left(\frac{L}{6}\right)^2 = \boxed{\frac{1}{9} mL^2}$$

(b) The rod is then released from rest from the horizontal position shown above. Calculate the linear speed of the bottom end of the rod when the rod passes through the vertical.

Handwritten: mechanical energy conserved

$$U_g = K_R + U_g$$

$$0 = mgh = \frac{1}{2} I \omega^2 - \left(\frac{m}{3}\right)(g)\left(\frac{L}{6}\right) + \left(\frac{2m}{3}\right)(g)\left(\frac{L}{3}\right)$$

$$0 = \frac{1}{2} \left(\frac{1}{9} mL^2\right) (\omega^2) - \frac{mgL}{18} + \frac{2mgL}{9} = \frac{mL^2 \omega^2}{18} + \frac{mgL}{9}$$

$$\frac{L^2 \omega^2}{18} = \frac{mgL}{9}$$

$$L \omega^2 = 3g$$

$$\omega^2 = \frac{3g}{L}$$


$$\omega = \sqrt{\frac{3g}{L}}$$

$$v = \omega r$$

$$v = \sqrt{\frac{3g}{L}} \left(\frac{2L}{3}\right)$$

$$v = \frac{2\sqrt{3gL}}{3}$$

GO ON TO THE NEXT PAGE.



- (c) The rod is brought to rest in the vertical position shown above and hangs freely. It is then displaced slightly from this position. Calculate the period of oscillation as it swings.

$$\omega = \sqrt{\frac{mgd}{I}} = \sqrt{\frac{mg \frac{L}{3}}{\frac{1}{3} mL^2}} = \sqrt{\frac{9mgL}{3mL^2}} = \sqrt{\frac{3g}{L}}$$

$$T = \frac{2\pi}{\omega} = 2\pi \sqrt{\frac{L}{3g}}$$