



AP[®] Physics C: Mechanics 2002 Free-Response Questions

The materials included in these files are intended for use by AP teachers for course and exam preparation in the classroom; permission for any other use must be sought from the Advanced Placement Program[®]. Teachers may reproduce them, in whole or in part, in limited quantities, for face-to-face teaching purposes but may not mass distribute the materials, electronically or otherwise. These materials and any copies made of them may not be resold, and the copyright notices must be retained as they appear here. This permission does not apply to any third-party copyrights contained herein.

These materials were produced by Educational Testing Service[®] (ETS[®]), which develops and administers the examinations of the Advanced Placement Program for the College Board. The College Board and Educational Testing Service (ETS) are dedicated to the principle of equal opportunity, and their programs, services, and employment policies are guided by that principle.

The College Board is a national nonprofit membership association dedicated to preparing, inspiring, and connecting students to college and opportunity. Founded in 1900, the association is composed of more than 4,200 schools, colleges, universities, and other educational organizations. Each year, the College Board serves over three million students and their parents, 22,000 high schools, and 3,500 colleges, through major programs and services in college admission, guidance, assessment, financial aid, enrollment, and teaching and learning. Among its best-known programs are the SAT[®], the PSAT/NMSQT[®], and the Advanced Placement Program[®] (AP[®]). The College Board is committed to the principles of equity and excellence, and that commitment is embodied in all of its programs, services, activities, and concerns.

Copyright © 2002 by College Entrance Examination Board. All rights reserved. College Board, Advanced Placement Program, AP, SAT, and the acorn logo are registered trademarks of the College Entrance Examination Board. APIEL is a trademark owned by the College Entrance Examination Board. PSAT/NMSQT is a registered trademark jointly owned by the College Entrance Examination Board and the National Merit Scholarship Corporation. Educational Testing Service and ETS are registered trademarks of Educational Testing Service.

TABLE OF INFORMATION FOR 2002

CONSTANTS AND CONVERSION FACTORS		UNITS		PREFIXES																																		
		Name	Symbol	Factor	Prefix	Symbol																																
1 unified atomic mass unit,	$1 \text{ u} = 1.66 \times 10^{-27} \text{ kg}$ $= 931 \text{ MeV}/c^2$	meter	m	10^9	giga	G																																
Proton mass,	$m_p = 1.67 \times 10^{-27} \text{ kg}$	kilogram	kg	10^6	mega	M																																
Neutron mass,	$m_n = 1.67 \times 10^{-27} \text{ kg}$	second	s	10^3	kilo	k																																
Electron mass,	$m_e = 9.11 \times 10^{-31} \text{ kg}$	ampere	A	10^{-2}	centi	c																																
Magnitude of the electron charge,	$e = 1.60 \times 10^{-19} \text{ C}$	kelvin	K	10^{-3}	milli	m																																
Avogadro's number,	$N_0 = 6.02 \times 10^{23} \text{ mol}^{-1}$	mole	mol	10^{-6}	micro	μ																																
Universal gas constant,	$R = 8.31 \text{ J}/(\text{mol} \cdot \text{K})$	hertz	Hz	10^{-9}	nano	n																																
Boltzmann's constant,	$k_B = 1.38 \times 10^{-23} \text{ J/K}$	newton	N	10^{-12}	pico	p																																
Speed of light,	$c = 3.00 \times 10^8 \text{ m/s}$	pascal	Pa	VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLES <table border="1"> <thead> <tr> <th>θ</th> <th>$\sin \theta$</th> <th>$\cos \theta$</th> <th>$\tan \theta$</th> </tr> </thead> <tbody> <tr> <td>0°</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>30°</td> <td>1/2</td> <td>$\sqrt{3}/2$</td> <td>$\sqrt{3}/3$</td> </tr> <tr> <td>37°</td> <td>3/5</td> <td>4/5</td> <td>3/4</td> </tr> <tr> <td>45°</td> <td>$\sqrt{2}/2$</td> <td>$\sqrt{2}/2$</td> <td>1</td> </tr> <tr> <td>53°</td> <td>4/5</td> <td>3/5</td> <td>4/3</td> </tr> <tr> <td>60°</td> <td>$\sqrt{3}/2$</td> <td>1/2</td> <td>$\sqrt{3}$</td> </tr> <tr> <td>90°</td> <td>1</td> <td>0</td> <td>∞</td> </tr> </tbody> </table>			θ	$\sin \theta$	$\cos \theta$	$\tan \theta$	0°	0	1	0	30°	1/2	$\sqrt{3}/2$	$\sqrt{3}/3$	37°	3/5	4/5	3/4	45°	$\sqrt{2}/2$	$\sqrt{2}/2$	1	53°	4/5	3/5	4/3	60°	$\sqrt{3}/2$	1/2	$\sqrt{3}$	90°	1	0	∞
θ	$\sin \theta$	$\cos \theta$	$\tan \theta$																																			
0°	0	1	0																																			
30°	1/2	$\sqrt{3}/2$	$\sqrt{3}/3$																																			
37°	3/5	4/5	3/4																																			
45°	$\sqrt{2}/2$	$\sqrt{2}/2$	1																																			
53°	4/5	3/5	4/3																																			
60°	$\sqrt{3}/2$	1/2	$\sqrt{3}$																																			
90°	1	0	∞																																			
Planck's constant,	$h = 6.63 \times 10^{-34} \text{ J} \cdot \text{s}$ $= 4.14 \times 10^{-15} \text{ eV} \cdot \text{s}$	joule	J																																			
	$hc = 1.99 \times 10^{-25} \text{ J} \cdot \text{m}$ $= 1.24 \times 10^3 \text{ eV} \cdot \text{nm}$	watt	W																																			
Vacuum permittivity,	$\epsilon_0 = 8.85 \times 10^{-12} \text{ C}^2/\text{N} \cdot \text{m}^2$	coulomb	C																																			
Coulomb's law constant,	$k = 1/4\pi\epsilon_0 = 9.0 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$	volt	V																																			
Vacuum permeability,	$\mu_0 = 4\pi \times 10^{-7} (\text{T} \cdot \text{m})/\text{A}$	ohm	Ω																																			
Magnetic constant,	$k' = \mu_0/4\pi = 10^{-7} (\text{T} \cdot \text{m})/\text{A}$	henry	H																																			
Universal gravitational constant,	$G = 6.67 \times 10^{-11} \text{ m}^3/\text{kg} \cdot \text{s}^2$	farad	F																																			
Acceleration due to gravity at the Earth's surface,	$g = 9.8 \text{ m/s}^2$	tesla	T																																			
1 atmosphere pressure,	$1 \text{ atm} = 1.0 \times 10^5 \text{ N/m}^2$ $= 1.0 \times 10^5 \text{ Pa}$	degree Celsius	$^\circ\text{C}$																																			
1 electron volt,	$1 \text{ eV} = 1.60 \times 10^{-19} \text{ J}$	electron-volt	eV																																			

The following conventions are used in this examination.

- I. Unless otherwise stated, the frame of reference of any problem is assumed to be inertial.
- II. The direction of any electric current is the direction of flow of positive charge (conventional current).
- III. For any isolated electric charge, the electric potential is defined as zero at an infinite distance from the charge.

ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2002

MECHANICS

$$v = v_0 + at$$

$$x = x_0 + v_0t + \frac{1}{2}at^2$$

$$v^2 = v_0^2 + 2a(x - x_0)$$

$$\sum \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$$

$$\mathbf{F} = \frac{d\mathbf{p}}{dt}$$

$$\mathbf{J} = \int \mathbf{F} dt = \Delta\mathbf{p}$$

$$\mathbf{p} = m\mathbf{v}$$

$$F_{fric} \leq \mu N$$

$$W = \int \mathbf{F} \cdot d\mathbf{r}$$

$$K = \frac{1}{2}mv^2$$

$$P = \frac{dW}{dt}$$

$$P = \mathbf{F} \cdot \mathbf{v}$$

$$\Delta U_g = mgh$$

$$a_c = \frac{v^2}{r} = \omega^2 r$$

$$\boldsymbol{\tau} = \mathbf{r} \times \mathbf{F}$$

$$\sum \boldsymbol{\tau} = \boldsymbol{\tau}_{net} = I\boldsymbol{\alpha}$$

$$I = \int r^2 dm = \sum mr^2$$

$$\mathbf{r}_{cm} = \sum m\mathbf{r} / \sum m$$

$$v = r\omega$$

$$\mathbf{L} = \mathbf{r} \times \mathbf{p} = I\boldsymbol{\omega}$$

$$K = \frac{1}{2}I\omega^2$$

$$\omega = \omega_0 + \alpha t$$

$$\theta = \theta_0 + \omega_0 t + \frac{1}{2}\alpha t^2$$

$$\mathbf{F}_s = -kx$$

$$U_s = \frac{1}{2}kx^2$$

$$T = \frac{2\pi}{\omega} = \frac{1}{f}$$

$$T_s = 2\pi\sqrt{\frac{m}{k}}$$

$$T_p = 2\pi\sqrt{\frac{\ell}{g}}$$

$$\mathbf{F}_G = -\frac{Gm_1m_2}{r^2} \hat{\mathbf{r}}$$

$$U_G = -\frac{Gm_1m_2}{r}$$

a = acceleration
 F = force
 f = frequency
 h = height
 I = rotational inertia
 J = impulse
 K = kinetic energy
 k = spring constant
 ℓ = length
 L = angular momentum
 m = mass
 N = normal force
 P = power
 p = momentum
 r = radius or distance
 \mathbf{r} = position vector
 T = period
 t = time
 U = potential energy
 v = velocity or speed
 W = work done on a system
 x = position
 μ = coefficient of friction
 θ = angle
 $\boldsymbol{\tau}$ = torque
 ω = angular speed
 α = angular acceleration

ELECTRICITY AND MAGNETISM

$$F = \frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r^2}$$

$$\mathbf{E} = \frac{\mathbf{F}}{q}$$

$$\oint \mathbf{E} \cdot d\mathbf{A} = \frac{Q}{\epsilon_0}$$

$$E = -\frac{dV}{dr}$$

$$V = \frac{1}{4\pi\epsilon_0} \sum_i \frac{q_i}{r_i}$$

$$U_E = qV = \frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r}$$

$$C = \frac{Q}{V}$$

$$C = \frac{\kappa\epsilon_0 A}{d}$$

$$C_p = \sum_i C_i$$

$$\frac{1}{C_s} = \sum_i \frac{1}{C_i}$$

$$I = \frac{dQ}{dt}$$

$$U_c = \frac{1}{2}QV = \frac{1}{2}CV^2$$

$$R = \frac{\rho\ell}{A}$$

$$V = IR$$

$$R_s = \sum_i R_i$$

$$\frac{1}{R_p} = \sum_i \frac{1}{R_i}$$

$$P = IV$$

$$\mathbf{F}_M = q\mathbf{v} \times \mathbf{B}$$

$$\oint \mathbf{B} \cdot d\boldsymbol{\ell} = \mu_0 I$$

$$\mathbf{F} = \int I d\boldsymbol{\ell} \times \mathbf{B}$$

$$B_s = \mu_0 nI$$

$$\phi_m = \int \mathbf{B} \cdot d\mathbf{A}$$

$$\mathcal{E} = -\frac{d\phi_m}{dt}$$

$$\mathcal{E} = -L\frac{dI}{dt}$$

$$U_L = \frac{1}{2}LI^2$$

A = area
 B = magnetic field
 C = capacitance
 d = distance
 E = electric field
 \mathcal{E} = emf
 F = force
 I = current
 L = inductance
 ℓ = length
 n = number of loops of wire per unit length
 P = power
 Q = charge
 q = point charge
 R = resistance
 r = distance
 t = time
 U = potential or stored energy
 V = electric potential
 v = velocity or speed
 ρ = resistivity
 ϕ_m = magnetic flux
 κ = dielectric constant

ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2002

GEOMETRY AND TRIGONOMETRY

Rectangle	A = area
$A = bh$	C = circumference
Triangle	V = volume
$A = \frac{1}{2}bh$	S = surface area
Circle	b = base
$A = \pi r^2$	h = height
$C = 2\pi r$	ℓ = length
Parallelepiped	w = width
$V = \ell wh$	r = radius

Cylinder
$V = \pi r^2 \ell$
$S = 2\pi r \ell + 2\pi r^2$


Sphere
$V = \frac{4}{3}\pi r^3$
$S = 4\pi r^2$

Right Triangle
$a^2 + b^2 = c^2$

$$\sin \theta = \frac{a}{c}$$

$$\cos \theta = \frac{b}{c}$$

$$\tan \theta = \frac{a}{b}$$



CALCULUS

$$\frac{df}{dx} = \frac{df}{du} \frac{du}{dx}$$

$$\frac{d}{dx}(x^n) = nx^{n-1}$$

$$\frac{d}{dx}(e^x) = e^x$$

$$\frac{d}{dx}(\ln x) = \frac{1}{x}$$

$$\frac{d}{dx}(\sin x) = \cos x$$

$$\frac{d}{dx}(\cos x) = -\sin x$$

$$\int x^n dx = \frac{1}{n+1} x^{n+1}, n \neq -1$$

$$\int e^x dx = e^x$$

$$\int \frac{dx}{x} = \ln|x|$$

$$\int \cos x dx = \sin x$$

$$\int \sin x dx = -\cos x$$

2002 AP[®] PHYSICS C: MECHANICS FREE-RESPONSE QUESTIONS

PHYSICS C Section II, MECHANICS

Time—45 minutes

3 Questions

Directions: Answer all three questions. The suggested time is about 15 minutes for answering each of the questions, which are worth 15 points each. The parts within a question may not have equal weight. Show all your work in the pink booklet in the spaces provided after each part, NOT in this green insert.


Mech 1.

A crash test car of mass 1,000 kg moving at constant speed of 12 m/s collides completely inelastically with an object of mass M at time $t = 0$. The object was initially at rest. The speed v in m/s of the car-object system after the collision is given as a function of time t in seconds by the expression

$$v = \frac{8}{1 + 5t}.$$

- Calculate the mass M of the object.
- Assuming an initial position of $x = 0$, determine an expression for the position of the car-object system after the collision as a function of time t .
- Determine an expression for the resisting force on the car-object system after the collision as a function of time t .
- Determine the impulse delivered to the car-object system from $t = 0$ to $t = 2.0$ s.

2002 AP[®] PHYSICS C: MECHANICS FREE-RESPONSE QUESTIONS



Mech 2.

The cart shown above is made of a block of mass m and four solid rubber tires each of mass $m/4$ and radius r . Each tire may be considered to be a disk. (A disk has rotational inertia $\frac{1}{2} ML^2$, where M is the mass and L is the radius of the disk.) The cart is released from rest and rolls without slipping from the top of an inclined plane of height h . Express all algebraic answers in terms of the given quantities and fundamental constants.

- (a) Determine the total rotational inertia of all four tires.
- (b) Determine the speed of the cart when it reaches the bottom of the incline.
- (c) After rolling down the incline and across the horizontal surface, the cart collides with a bumper of negligible mass attached to an ideal spring, which has a spring constant k . Determine the distance x_m the spring is compressed before the cart and bumper come to rest.
- (d) Now assume that the bumper has a non-negligible mass. After the collision with the bumper, the spring is compressed to a maximum distance of about 90% of the value of x_m in part (c). Give a reasonable explanation for this decrease.


2002 AP[®] PHYSICS C: MECHANICS FREE-RESPONSE QUESTIONS

Mech 3.

An object of mass 0.5 kg experiences a force that is associated with the potential energy function

$$U(x) = \frac{4.0}{2.0 + x}, \text{ where } U \text{ is in joules and } x \text{ is in meters.}$$

(a) On the axes below, sketch the graph of $U(x)$ versus x .



(b) Determine the force associated with the potential energy function given above.

(c) Suppose that the object is released from rest at the origin. Determine the speed of the particle at $x = 2$ m.

In the laboratory, you are given a glider of mass 0.5 kg on an air track. The glider is acted on by the force determined in part (b). Your goal is to determine experimentally the validity of your theoretical calculation in part (c).

(d) From the list below, select the additional equipment you will need from the laboratory to do your experiment by checking the line next to each item. If you need more than one of an item, place the number you need on the line.

Meterstick Stopwatch Photogate timer String Spring
 Balance Wood block Set of objects of different masses

(e) Briefly outline the procedure you will use, being explicit about what measurements you need to make in order to determine the speed. You may include a labeled diagram of your setup if it will clarify your procedure.

END OF SECTION II, MECHANICS