




AP Physics C: Mechanics 2000 Student Samples

The materials included in these files are intended for non-commercial use by AP teachers for course and exam preparation; permission for any other use must be sought from the Advanced Placement Program. Teachers may reproduce them, in whole or in part, in limited quantities, for face-to-face teaching purposes but may not mass distribute the materials, electronically or otherwise. These materials and any copies made of them may not be resold, and the copyright notices must be retained as they appear here. This permission does not apply to any third-party copyrights contained herein.

These materials were produced by Educational Testing Service (ETS), which develops and administers the examinations of the Advanced Placement Program for the College Board. The College Board and Educational Testing Service (ETS) are dedicated to the principle of equal opportunity, and their programs, services, and employment policies are guided by that principle.

The College Board is a national nonprofit membership association dedicated to preparing, inspiring, and connecting students to college and opportunity. Founded in 1900, the association is composed of more than 3,900 schools, colleges, universities, and other educational organizations. Each year, the College Board serves over three million students and their parents, 22,000 high schools, and 3,500 colleges, through major programs and services in college admission, guidance, assessment, financial aid, enrollment, and teaching and learning. Among its best-known programs are the SAT[®], the PSAT/NMSQT[™], the Advanced Placement Program[®] (AP[®]), and Pacesetter[®]. The College Board is committed to the principles of equity and excellence, and that commitment is embodied in all of its programs, services, activities, and concerns.


Copyright © 2001 by College Entrance Examination Board. All rights reserved. College Board, Advanced Placement Program, AP, and the acorn logo are registered trademarks of the College Entrance Examination Board.



Mech 3.

A pulley of radius R_1 and rotational inertia I_1 is mounted on an axle with negligible friction. A light cord passing over the pulley has two blocks of mass m attached to either end, as shown above. Assume that the cord does not slip on the pulley. Determine the answers to parts (a) and (b) in terms of m , R_1 , I_1 , and fundamental constants.

(a) Determine the tension T in the cord.




$$\sum F = 0 = W - T$$

$$T = W = 2mg$$

M M M M M M M M M M M M M M M

- (b) One block is now removed from the right and hung on the left. When the system is released from rest, the three blocks on the left accelerate downward with an acceleration $\frac{g}{3}$. Determine the following.



- i. The tension T_3 in the section of cord supporting the three blocks on the left

$$\Sigma F = 3ma = W_3 - T_3$$

$$\frac{3mg}{3} = 3mg - T_3$$

$$T_3 = 3mg - \frac{mg}{3} = 2mg$$

- ii. The tension T_1 in the section of cord supporting the single block on the right



Acceleration along rope is equal at both ends

$$\Sigma F = ma = T_1 - W$$

$$T_1 = \frac{mg}{3} + mg = \frac{4}{3}mg$$

- iii. The rotational inertia I_1 of the pulley



$$\tau_{net} = I_1 \alpha = \tau_{T_3} - \tau_{T_1}$$


$$I_1 \frac{a}{R_1} = T_3 R_1 - T_1 R_1$$

$$\frac{I_1 a}{R_1} = 2mg R_1 - \frac{4}{3}mg R_1$$

$$\frac{I_1 g}{3R_1} = \frac{2}{3}mg R_1$$

$$I_1 = 2m R_1^2$$

GO ON TO THE NEXT PAGE.



(c) The blocks are now removed and the cord is tied into a loop, which is passed around the original pulley and a second pulley of radius $2R_1$ and rotational inertia $16I_1$. The axis of the original pulley is attached to a motor that rotates it at angular speed ω_1 , which in turn causes the larger pulley to rotate. The loop does not slip on the pulleys. Determine the following in terms of I_1 , R_1 , and ω_1 .

i. The angular speed ω_2 of the larger pulley


$$\begin{aligned}
 \omega_1 &= \frac{v_{\text{cord}}}{R_1} & v_{\text{cord}} &= \text{constant} \\
 v_{\text{cord}} &= \omega_1 R_1 & \omega_2 &= \frac{v_{\text{cord}}}{R_2} = \frac{\omega_1 R_1}{2R_1} = \frac{\omega_1}{2}
 \end{aligned}$$

ii. The angular momentum L_2 of the larger pulley

$$\begin{aligned}
 L_2 &= I_2 \omega_2 \\
 &= (16 I_1) \left(\frac{\omega_1}{2} \right) \\
 &= 8 I_1 \omega_1
 \end{aligned}$$

iii. The total kinetic energy of the system

$$\begin{aligned}
 K_{\text{tot}} &= K_{\text{rot1}} + K_{\text{rot2}} \\
 &= \frac{1}{2} I_1 \omega_1^2 + \frac{1}{2} I_2 \omega_2^2 \\
 &= \frac{1}{2} I_1 \omega_1^2 + \frac{1}{2} (16 I_1) \left(\frac{\omega_1}{2} \right)^2 \\
 &= \frac{1}{2} I_1 \omega_1^2 + 2 I_1 \omega_1^2 \\
 &= \frac{5}{2} I_1 \omega_1^2
 \end{aligned}$$



(c) The blocks are now removed and the cord is tied into a loop, which is passed around the original pulley and a second pulley of radius $2R_1$ and rotational inertia $16I_1$. The axis of the original pulley is attached to a motor that rotates it at angular speed ω_1 , which in turn causes the larger pulley to rotate. The loop does not slip on the pulleys. Determine the following in terms of I_1 , R_1 , and ω_1 .

i. The angular speed ω_2 of the larger pulley

ii. The angular momentum L_2 of the larger pulley


$$L = I\omega$$

iii. The total kinetic energy of the system

~~$$KE = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2$$~~

$$K = \frac{1}{2}I_1\omega_1^2 + \frac{1}{2}I_2\omega_2^2$$


N1



Mech 3.

A pulley of radius R_1 and rotational inertia I_1 is mounted on an axle with negligible friction. A light cord passing over the pulley has two blocks of mass m attached to either end, as shown above. Assume that the cord does not slip on the pulley. Determine the answers to parts (a) and (b) in terms of m , R_1 , I_1 , and fundamental constants.

(a) Determine the tension T in the cord.



System

$$\sum F = ma$$

$$W_1 - W_2 = ma$$

$$2mg - 2mg = ma$$

$$0 = ma$$

$$a = 0$$



$$\sum F = 0$$

$$W - T = 0$$

$$W = T$$

$$2mg = T$$

GO ON TO THE NEXT PAGE.

(b) One block is now removed from the right and hung on the left. When the system is released from rest, the three blocks on the left accelerate downward with an acceleration $\frac{8}{3}$. Determine the following.

i. The tension T_3 in the section of cord supporting the three blocks on the left



$$\sum F = ma$$

$$T_3 - w_3 = \frac{mg}{3}$$

$$3mg - T_3 = \frac{mg}{3}$$

$$3mg - \frac{mg}{3} = T_3$$

$$\frac{8}{3}mg = T_3$$

ii. The tension T_1 in the section of cord supporting the single block on the right



$$\sum F = ma$$

$$T_1 - w_1 = \frac{mg}{3}$$

$$T_1 = mg - \frac{mg}{3}$$

$$T_1 = \frac{2}{3}mg$$

iii. The rotational inertia I_1 of the pulley

$$\sum \tau = I \alpha$$

$$R_1 \times T_3 - R_1 \times T_1 = I \alpha$$

$$\frac{8}{3}R_1 mg - \frac{2}{3}R_1 mg = I \alpha$$


$$2R_1 mg = I \alpha$$

$$I = \frac{2R_1 mg}{\alpha}$$

$$= \frac{2R_1 mg}{\frac{2R_1 mg}{6R_1 m}} = \frac{2R_1^2 mg}{\frac{2R_1 mg}{6R_1 m}}$$

$$I = 6R_1 m$$

GO ON TO THE NEXT PAGE.



(c) The blocks are now removed and the cord is tied into a loop, which is passed around the original pulley and a second pulley of radius $2R_1$ and rotational inertia $16I_1$. The axis of the original pulley is attached to a motor that rotates it at angular speed ω_1 , which in turn causes the larger pulley to rotate. The loop does not slip on the pulleys. Determine the following in terms of I_1 , R_1 , and ω_1 .

i. The angular speed ω_2 of the larger pulley

ii. The angular momentum L_2 of the larger pulley

iii. The total kinetic energy of the system